

**M-200-CT**

# BRICK WHEELBARROW

## Brick wheelbarrow with puncture proof tyre, capacity 200 Kg.

M-200-CT brick wheelbarrow with puncture proof tyre.

Loadcapacity: 60-bricks.

Handle height: 500mm.

Height: front end 540mm.

Steel rim with double closed ball bearings.

Puncture proof tire (foamed polyurethane).

Wear pads to extend the lifetime of the legs.

Ergonomic natural rubber handles especially devised to the form of your hand.

Finished with a powder coating in grey. (no solvents, less harmful to the environment).



10910  
M-200-CT

- \* Oval tube (lighter and stronger).
- \* Natural rubber handle especially the shape of your hand.
- \* Puncture proof tyre (foamed polyurethane).
- \* Steel rim with double sealed ball bearings.



11264  
M-970-Z-RUB



11189  
M-800-CT

Cap. (kg)	Dimensions overall LxWxH (mm)	Dimensions platform LxWxH (mm)	Weight (kg)	Height front-end (mm)	Wheel Ø(mm)	Wheels	Colour frame	Handgrip LxW (mm)	Article	Article-nr
200	1440x600x940	450x450	18,6	540	400	Puncture proof	Gray	38x20	M-200-CT	10910
200	400x100		3,4		400	Puncture proof			M-800-CT	11189
	130x55x38		0,11					38x20	M-970-Z RUB	11264