

SPRINT TL

Bravi's upgraded version of its one of a kind order picker specifically designed for handling tires

- **Extended Battery Life:** premium 245 Ah battery pack granting a longer working cycle between charges
- **Exceptional maneuverability:** compact size and light design combined with a 5.00 mt working height
- **Upgraded Tire Lift Compartment:** fully motorized compartment with an increased 150 kg capacity, ideal also for SUV tires
- **Super Low Running Costs:** Reduced operating costs, maintenance free mast and superior standard warranty package



EFFICIENT AND VERSATILE

SPRINT TL lifts the operator and tires, easily positioning them at the desired height and allowing for a faster and safer performance than if manually handled. The capacity on the tires compartment has increased to 150 kg to also allow SUV tires up to 800 mm diameter to fit. The forks lower all the way down to the floor, to easily pick up the stack of tires and the wheel round dolly included. In addition, the forks are foldable, to maintain a very compact footprint.

SAFE

Hand sensors and dual footswitches on the platform ensure the correct position of the operator while actively onboard using the lifting functions. The heavy duty steel case construction and frame allow to the operator to safely handling tires up to 150 kg, avoiding the risk of injuries related to manual movement. To grant a smoother picking and loading process, the tires compartment is fully motorized.

DURABLE

Simple, efficient, and comfortable the SPRINT TL is the result of continuous technical improvements. The innovative lifting mast requires no upkeep, while the careful selection of high-quality components, and an extremely simple yet effective design make the SPRINT TL virtually maintenance-free, designed to guarantee low ownership costs.

"The Sprint TL is the innovative piece of equipment for handling tires safer, faster and more efficiently."



Measurements

A	Working Height	5000 mm	Platform capacity	130 kg
B	Platform Height	3000 mm	Weight (CE)	820 kg
C	Stowed unit height	1515 mm	Rated n° of occupants (CE)	1
D	Tot. unit length (forks ext.)	2275 mm	Drive Speed Stowed	5 km/h
	Tot. unit length (forks stow.)	1778 mm		
E	Unit height - with stowed tire holder	1665 mm	Drive Speed Elevated	1.2 km/h
F	Unit height - with elevated tire holder	1914 mm	Gradeability while elevated	T.L. 2°
				TLP 1.5°
G	Tot. unit width	809 mm	Inside turning radius	ZERO
H	Entry Step	394 mm	Outside turning radius	2250 mm
I	Lift compartment Capacity	150 kg	Power Source	110/220 V ca 24Vcc
L	Lift compartment Width	400 mm	Batteries	n° 4 - 6V; 245Ah@20h

