



NEW !



FEATURES

Latest technology

- **Brushless motor**-ZAPAK patented single motor design provides extremely long service life.
- **Li-Ion battery**- 18V 3000mAh high capacity rechargeable battery and **Bosch** 30 minutes charger.

Powerful & Speedy

- Max. tension **400 KGS (4000N)** - **ZP96A** heavy duty model.
- Max. tension **250 KGS (2500N)** - **ZP92A** standard duty model.
- **Patented strap grippers design** contributes to high tension ability.
- **One-handed operation** performs automatic tensioning, friction welding and cutting efficiently.

Smart & Easy

- **Pre-programmed touch panel** with digital signal to suit different operation needs instinctively.
- **Lightest** model in same class of tools approx. 3.46kg only (7.60lbs incl. battery) relieves operation fatigue.
- Special tool retreating device ensures smooth and **easy removal of tool**.
- **Unique rear-end roller** design prevents scratches or worn out damages on strapping objects.
- **User self-adjustable strap widths guiders** and self-changeable wearing parts.
- **Optional hanger** reduces operation fatigue.
- **Soft mode** device facilitates lighter strapping tension force for light packages or fragile objects.

Safety

- One-handed operation **conforms to CE safety directive** and meets RoHS requirements.
- **Li-Ion battery complies with UN38.3** safety requirements.

MODEL NUMBER & SPECIFICATIONS :

Model No.	Fits Poly-Strap	Strap Width		Strap Thickness		Tension Range	Sealing Efficiency	Dimension & Weight
		mm	inch	mm	Inch			
ZP92A	PP	9~16	3/8~5/8	0.55~1.35	0.022~0.053	10 ~250kgs (22~550Lbs)	85+-5%	Approx. 33 x 15x 12.5 cm (13 x 6 x 5 inch)
	PET							Tool Weight
ZP96A	PP	16&19	5/8&3/4	0.75~1.35	0.029~0.053	40~400kgs (88~880Lbs)	85+-5%	Approx. 2.80kgs (6.16Lbs)
	PET			0.65~1.35	0.026~0.053			Battery Weight Approx. 0.66kgs (1.45Lbs)

- Bosch charger A/C voltage 100V, 115V, 230V, 240V available for different markets demand.
- Sealing time adjustment: 0.4 ~ 2.0 seconds.
- Li-Ion battery life is up to 2000 charges with proper charging and discharging habits.
- Fully charged Li-Ion battery supports up to max. 600 cycles (PP) dependant on straps quality, tension setting and sealing time setting.

<Remarks>

- Tension performance and sealing efficiency vary based on battery capacity, strap specifications & quality.
- Softer or thinner straps may require different cutter. Please consult with your dealer if needed.